










1 3/4" CTS - FACE & GUTTER COMBINATIONS

			GUTTERS				
			5/8"	2"	2 5/8"	4 1/8"	
							
			INFILL THICKNESS	10-205	10-207	10-209	
5/8"	FACE 10-111		1"		3 7/8"	4 1/2"	6"
1 1/4"	FACE 10-113		1"		4 1/2"	5 1/8"	6 5/8"
* 1 1/2"	FACE 10-114		1"		4 3/4"	5 3/8"	6 7/8"
2"	FACE 10-115		1"		5 1/4"	5 7/8"	7 3/8"
COMMON MULLIONS							
				10-102	10-206	10-208	10-212

1 1/4" CTS - FACE & GUTTER COMBINATIONS

			GUTTERS			
			5/8"	2"	2 5/8"	
						
			INFILL THICKNESS	10-215	10-213	10-211
5/8"	FACE 10-011		1"	2 1/2"	3 7/8"	4 1/2"
			1/4"	1 3/4"	3 1/8"	3 3/4"
1 1/4"	FACE 10-013		1"	3 1/8"	4 1/2"	5 1/8"
			1/4"	2 3/8"	3 3/4"	4 3/8"
2"	FACE 10-015		1"	3 7/8"	5 1/4"	5 7/8"
			1/4"	3 1/8"	4 1/2"	5 1/8"

NOTE:
1 1/4" PERIMETER INFILL ACCOMMODATES: 1/8", 1/4", 1/2", 5/8", 7/8", 1"
1 3/8" & 1 3/4" INFILL IS POSSIBLE WITH SPECIAL ADAPTORS
USE 10-250 T-BLOCK FOR 1/4" INFILL
USE 10-100 T-BLOCK FOR 1" INFILL
* DENOTES NON-STOKED PART

 - STANDARD SYSTEM DEPTH