



Handler & HD Handler

HD Handler has been a leader in the hand film industry for generations. It is superior in load retention, puncture resistance, cling, film memory and is intended for extreme applications requiring critical load security in various environments. **Upgrade Handler & HD Handler with UVI, VCI, Static-Dissipative, or Color Additives.**

Film	Dimension	CS/RL/PLT
Handler	3" X 1000' X .0008"	18 RL/CS ; 60 CS/PLT
	5" X 1000' X .0008"	12 RL/CS ; 60 CS/PLT
	12" X 2100' X .0006"	4 RL/CS ; 60 CS/PLT
	12" X 1500' X .0007"	4 RL/CS ; 60 CS/PLT
	12" X 1500' X .0008"	4 RL/CS ; 60 CS/PLT
	15" X 2000' X .0006"	4 RL/CS ; 48 CS/PLT
	15" X 1500' X .0007"	4 RL/CS ; 48 CS/PLT
	15" X 1500' X .0008"	4 RL/CS ; 48 CS/PLT
	18" X 2000' X .0006"	4 RL/CS ; 36 CS/PLT
	18" X 1500' X .0007"	4 RL/CS ; 36 CS/PLT
	18" X 1500' X .0008"	4 RL/CS ; 36 CS/PLT
HD Handler	12" X 1500' X .0009"	4 RL/CS ; 60 CS/PLT
	12" X 1500' X .0010"	4 RL/CS ; 60 CS/PLT
	12" X 1000' X .0012"	4 RL/CS ; 60 CS/PLT
	15" X 1500' X .0009"	4 RL/CS ; 48 CS/PLT
	15" X 1500' X .0010"	4 RL/CS ; 48 CS/PLT
	15" X 1000' X .0012"	4 RL/CS ; 48 CS/PLT
	18" X 1500' X .0009"	4 RL/CS ; 36 CS/PLT
	18" X 1500' X .0010"	4 RL/CS ; 36 CS/PLT
	18" X 1000' X .0012"	4 RL/CS ; 36 CS/PLT

Stretch Film

Machine

Legacy



Legacy is a blown machine film which provides ultimate load containment due to its powerful cling, memory, and puncture resistance. This multi-layer film is manufactured with auto-gauge and extrusion control technology which guarantees Legacy's high versatility, performance, and dependability.

We offer specific gauges based on application, load type, environment, and your machinery. Norflex Sales Specialists can help recommend which film is best for your specific needs.

Premium-grade additives available: UVI, VCI, static-dissipative, and colors.

20" X 8000' X .0006"
20" X 6500' X .0007"
20" X 6000' X .0008"

40 RLS/PLT

20" X 5000' X .0009"

20" X 4500' X .0010"

20" X 4200' X .00115"

20" X 4000' X .0012"

Custom sizes available on request.

Minimums apply.

20 RLS PLT


30" X 8000' X .0006" 30" X 6500' X .0007" 30" X 6000' X .0008" 30" X 5000' X .0009" 30" X 4500' X .0010"

30" X 4200' X .00115"

30" X 4000' X .0012"



Classic Cast



Classic Cast hand film is a generalpurpose cast co-extruded stretch film. **Classic Cast** provides excellent performance when wrapping most A and B type loads.

Quiet and Clear makes this film a great choice for most applications.

Classic 15"

15" x 1,500' x .0007" 48 RLS/PLT

15" x 1,500' x .0008" 48 RLS/PLT

15" x 1,500' x .0009" 48 RLS/PLT

15" x 1,000' x .0010" 48 RLS/PLT

15" x 1.000' x .0012" 48 RLS/PLT

Classic 18"

18" x 1,500' x .0007" 36 RLS/PLT

18" x 1,500' x .0008" 36 RLS/PLT

18" x 1,500' x .0009" 36 RLS/PLT

18" x 1,000' x .0010" 36 RLS/PLT

18" x 1,000' x .0012" 36 RLS/PLT



Pro-Cast

Pro-Cast, a one-sided cling machine film, is designed for a variety of applications. **Pro-Cast** offers two performance levels.

Our **Standard Blend** offers up 225% stretch, which covers most A and B type loads.

When a higher level of stretch is needed, our **Performance Blend** offers a greater level of stretch.

Both levels are clear and quiet.



Standard

19.7" x 6,500' x .0007" 40 RLS/PLT

19.7" x 6,000' x .0008" 40 RLS/PLT

19.7" x 5,000' x .0009" 40 RLS/PLT

19.7" x 3,500' x .0010" 40 RLS/PLT

29.5" & other sizes available.

Performance

19.7" x 6,000' x .00063" 40 RLS/PLT

19.7" x 9,000' x .00061" 40 RLS/PLT

19.7" x 8,000' x .00055" 40 RLS/PLT

19.7" x 9,000' x .00051" 40 RLS/PLT

29.5" & other sizes available.

Custom Shrink Bundling

Customizable to exceed any L-bar sealer or high-speed over-wrap shrink tunnel system.



SecureWrap has a lower seal temperature to increase savings. It also allows tighter packaging for less material waste.

OverWrap is designed for film over film applications.

- Customizable T/D shrink
- Low shrink and seal temperatures

MailWrap Postal Poly

MailWrap is a Postal-Approved film certified under the USPS-T-3204 test procedure. Produced with special attention to clarity, strength, and uniformity, **MailWrap** provides maximum uptime and throughput.

Norflex Inc. utilizes state-of-the-art auto-gauge and extrusion control technology to provide increased yield, uptime, and uniformity on all films.



Custom availability for a variety of colors, additives, and converter grade films. Norflex Inc. provides competitive lead times to ensure your operational deadlines are met.

Specialty Films

- Lamination Film
- Form, Fill, Seal (FFS)
- Mulch Film
- Industrial Sheeting
- · Custom: 300% Stretch Film
- Compression Film
- Converter-Grade Film
- Fiberglass Roving
- Roll Wrap





Premium-Grade Additives

- VCI for anti-corrosion applications
- UVI—A powerful 12-month UV inhibitor for outdoor storage
- Static-dissipative protection for static- and combustion-sensitive applications
- Complete line of custom colors

Manufacturing Capabilities

- Standard materials: LDPE, LLDPE, MDPE, EVA, and custom formulations
- Co-extruded film
- Width: 3"-100"
- Thickness: 60ga.-6mil
- Jumbo rolls: Up to 43" OD
- Cores: 3" I.D. or 6" I.D.
- Pre-stretch
- In-line slitting
- Venting



About Norflex, Inc.

Norflex, Inc. is a custom film **manufacturer** that specializes in high-quality stretch, shrink, custom additives, and converter-grade films used for industrial packaging and agricultural applications.

In 1992, owner and industry pioneer Arne Anderson established Norflex, Inc. to engineer high-quality polyethylene films. With continuous improvements in film manufacturing technology, the Norflex team delivers high-performing films with lead times that are consistently the shortest in the industry.

720 Norflex Drive Hudson, WI 54016

P: 800-556-0887 F: 715-386-7123

E: info@norflex.com

www.norflex.com

